



## HBR LED HIGH BAR *Altitude Adjustment*



The All New, Precision Crafted,  
Highest Performance  
LED High Bay .....

## Bar None

- Highest Mounting Heights
  - 138 Fixture Lumens Per Watt Attainable
  - Wide Ambient Operating Ranges, -30 C to 55C+
- Lensing Options: Clear - Frosted - Polycarbonate, Wire Guard
- Countless Lumen Packages... 9,000 Lumens to 75,000 + Lumens
- Easy mounting / Easy Handling / Easy board / driver access
  - Most Flexibility: Direct, Indirect, Direct/Indirect
    - Very Low 2.5" profile / 2' and 4' Light Bars
      - Distributions: Wide - Narrow
      - Multiple Sensor Options

*Sustainable LED Lighting Solutions*

# HBR LED High Bay / Low Bay

| LUMEN PACKAGE<br>2FT<br>FIXTURES | LUMENS<br>NO LENS<br>MAX AMB<br>=55c | LUMENS<br>W / FA LENS<br>MAX<br>AMB=55C | LUMENS<br>W / CL LENS<br>MAX<br>AMB=55C | LUMENS<br>W / CP LENS<br>MAX<br>AMB=55C | LUMENS<br>W / NB LENS<br>MAX<br>AMB=55C | Wattage<br>120V / 277V |
|----------------------------------|--------------------------------------|---|---|---|---|------------------------|
| 2-bar 94L-4K                     | 9,365                                | 8,103                                   | 9,089                                   | 9,020                                   | 7,246                                   | 71W / 69W              |
| 2-bar 94L-5K                     | 9,489                                | 8,210                                   | 9,209                                   | 9,139                                   | 7,341                                   | 71W / 69W              |
| 2-bar 126L-4K                    | 12,571                               | 10,877                                  | 12,200                                  | 12,108                                  | 9,726                                   | 94W / 92W              |
| 2-bar 126L-5K                    | 12,695                               | 10,985                                  | 12,321                                  | 12,228                                  | 9,822                                   | 94W / 92W              |
| 3-bar 189L-4K                    | 18,855                               | 16,316                                  | 18,301                                  | 18,162                                  | 14,589                                  | 140W / 138W            |
| 3-bar 189L-5K                    | 19,044                               | 16,477                                  | 18,482                                  | 18,341                                  | 14,733                                  | 140W / 138W            |
| 4-bar 251L-4K                    | 25,142                               | 21,755                                  | 24,401                                  | 24,216                                  | 19,452                                  | 187W / 184W            |
| 4-bar 251L-5K                    | 25,390                               | 21,969                                  | 24,642                                  | 24,455                                  | 19,644                                  | 187W / 184W            |
| 5-bar 314L-4K                    | 31,425                               | 27,193                                  | 30,501                                  | 30,269                                  | 24,315                                  | 234W / 230W            |
| 5-bar 314L-5K                    | 31,740                               | 27,462                                  | 30,803                                  | 30,569                                  | 24,555                                  | 234W / 230W            |

| 4FT<br>FIXTURES    |        |        |        |        |        |             |
|--------------------|--------|--------|--------|--------|--------|-------------|
| 2-bar 251L--<br>4K | 25,142 | 21,755 | 24,401 | 24,216 | 19,452 | 187W / 184W |
| 2-bar 251L--<br>5K | 25,390 | 21,969 | 24,642 | 24,455 | 19,644 | 187W / 184W |
| 3-bar 377L-4K      | 37,713 | 32,632 | 36,601 | 36,323 | 29,178 | 281W / 276W |
| 3-bar 377L-5K      | 38,085 | 32,954 | 36,963 | 36,683 | 29,466 | 281W / 276W |
| 4-bar 503L-4K      | 50,284 | 43,509 | 48,802 | 48,431 | 38,904 | 374W / 368W |
| 4-bar 503L-5K      | 50,780 | 43,939 | 49,284 | 48,723 | 39,288 | 374W / 368W |
| 5-bar 629L-4K      | 62,855 | 54,386 | 61,002 | 60,539 | 48,630 | 468W / 460W |
| 5-bar 629L-5K      | 63,480 | 54,924 | 66,282 | 61,138 | 49,110 | 468W / 460W |
| 6-bar 754L-4K      | 75,426 | 65,263 | 73,203 | 72,647 | 58,357 | 562W / 552W |
| 6-bar 754L-5K      | 76,170 | 65,908 | 73,926 | 73,365 | 58,933 | 562W / 552W |

- Low profile luminaire designed for high bay or low bay commercial/industrial applications.
- Use in warehouses, factories, assembly operations, hangars, big box retail, aisle lighting, sports facilities like gyms, tennis courts, field houses.

