



## HBR LED High Bar *Altitude Adjustment*



The All New, Precision Crafted,  
Highest Performance  
LED High Bay .....

## Bar None

- Highest Mounting Heights
  - 138 Fixture Lumens Per Watt Attainable
  - Wide Ambient Operating Ranges, -30 C to 55C+
- Lensing Options: Clear - Frosted - Polycarbonate, Wire Guard
- Countless Lumen Packages... 9,000 Lumens to 75,000 + Lumens
- Easy mounting / Easy Handling / Easy board / driver access
  - Most Flexibility: Direct, Indirect, Direct/Indirect
    - Very Low 2" profile / 2' and 4' Light Bars
      - Distributions: Wide - Narrow
      - Multiple Sensor Options

*Sustainable LED Lighting Solutions*

# HBR LED High Bay / Low Bay

LUMEN	LUMENS	LUMENS	LUMENS	LUMENS	LUMENS	LUMENS		
PACKAGE	NO LENS	W / FA LENS	W / CA LENS	W / CP LENS	W / ND LENS	W / WIREGUARD	Wattage	EFFICACY
2FT FIXTURES	MAX AMB=55c	MAX AMB=55C	MAX AMB=55C	MAX AMB=55C	MAX AMB=53C	MAX AMB=55C	277V	NO LENS
2-bar 94L-4K	9403 ***	8611 ***	9106 ***	8809 ***	7325 ***	8611 ***	69W	136 LPW
2-bar 94L-5K	9496 ***	8697 ***	9196***	8896 ***	7397 ***	8697 ***	69W	137 LPW
2-bar 126L-4K	12571 ***	11513 ***	12174 ***	11777 ***	9792 ***	11513 ***	92W	137 LPW
2-bar 126L-5K	12695 ***	11626 ***	12294 ***	11893 ***	9889 ***	11626 ***	92W	138 LPW
3-bar 189L-4K	18885 ***	17269 ***	18261 ***	17666 ***	14688 ***	17269 ***	138W	137 LPW
3-bar 189L-5K	19260 ***	17439 ***	18441 ***	17840 ***	14833 ***	17439 ***	138W	140 LPW
4-bar 251L-4K	25142 ***	23025 ***	24348 ***	23554 ***	19584 ***	23025 ***	184W	137 LPW
4-bar 251L-5K	25390 ***	23252 ***	24589 ***	23787 ***	19778 ***	23252 ***	184W	138 LPW
5-bar 314L-4K	31,425	28,781	30,435	29,443	24,481	28,781	230W	137 LPW
5-bar 314L-5K	31,740	29,066	30,736	29,734	24,723	29,066	230W	138 LPW
4FT FIXTURES								
2-bar 251L--4K	25142 ***	23,025	24,348	23,554	19,584	23,025	184W	137 LPW
2-bar 251L--5K	25390 ***	23,252	24,589	23,787	19,778	23,252	184W	138 LPW
3-bar 377L-4K	37810 ***	34,680	36,522	35,311	29,375	34,680	276W	137 LPW
3-bar 377L-5K	38085 ***	34,878	36,883	35,680	29,667	34,878	276W	138 LPW
4-bar 503L-4K	50284 ***	46,049	48,697	47,108	39,168	46,049	368W	137 LPW
4-bar 503L-5K	50780 ***	46,505	49,178	47,574	39,556	46,505	368W	138 LPW
5-bar 629L-4K	62,855	57,562	60,870	58,796	48,961	57,562	460W	137 LPW
5-bar 629L-5K	63,480	58,131	61,472	59,467	49,445	58,131	460W	138 LPW
6-bar 754L-4K	75,426	69,074	73,044	70,662	58,753	69,074	552W	137 LPW
6-bar 754L-5K	76,170	69,694	73,699	71,296	59,280	69,694	552W	138 LPW
*** Indicates 60° C MAX								

- Low profile luminaire designed for high bay or low bay commercial/industrial applications.
- Use in warehouses, factories, assembly operations, hangars, big box retail, aisle lighting, sports facilities like gyms, tennis courts, field houses.

