

JOB _____
 TYPE _____
 CATALOG # _____



TPLX SERIES

APPLICATION

- COMPLETELY SELF-CONTAINED, LOW PROFILE DESIGN WITH PUSH TO TEST SWITCH.
- FULLY AUTOMATIC OPERATION WITH LOW VOLTAGE DISCONNECT (LVD).
- CHARGE RATE/POWER ON LED INDICATOR.
- UNIVERSAL MOUNTING CANOPY FOR SIDE OR TOP INSTALLATION.
- LED LAMP LIFE OF 25 YEARS.

CONSTRUCTION

- INJECTION MOLDED, V-O FLAME RETARDANT, HIGH-IMPACT, THERMOPLASTIC HOUSING.
- ALL HARDWARE INCLUDED.
- DIRECTIONAL INDICATORS AND BACK PLATE SNAP INTO PLACE.

FINISH

- AVAILABLE IN NEUTRAL OR BLACK FINISH.

ELECTRICAL

- ENERGY EFFICIENT RED OR GREEN LED CONSUMES LESS THAN 4 WATTS.
- 120 OR 277 VAC OPERATION.
- DUAL CIRCUIT OPERATION AVAILABLE.



LISTED AND



LISTED FOR DAMP LOCATIONS. MEETS NEC REQUIREMENTS, UL924, AND NFPA 101 LIFE SAFETY CODE.



THERMOPLASTIC LED EXIT SIGN

ORDERING GUIDE

SERIES	NO. OF FACES	CANOPY	LETTER COLOR	HSG. COLOR		OPTIONS
TPLX	2	U	R G	W	<p>FACES: 2 - UNIVERSAL (SINGLE/DOUBLE)</p> <p>CANOPY: U - UNIVERSAL MOUNT</p> <p>LETTER COLOR: R - RED G - GREEN</p> <p>HSG. COLORS: W - WHITE B - BLACK</p>	<p>EM - NI-CAD BATTERY EMERG BACKUP SD - SELF DIAGNOSTIC RC - REMOTE CAPABLE (11 WATT MAX) USA - ASSEMBLED IN THE UNITED STATES</p> <p>ACCESSORIES: EMWG-1 - 15" WIRE GUARD EMBG-1 - POLYCARBONATE SHIELD</p>

TPLX SERIES

GUARDS & SHEILDS



EMWG-2

WIRE GUARDS			
Part #	H	W	D
EMWG-1	13 - 1/2"	15"	6"



POLYCARBONATE SHIELD			
Part #	H	W	D
EMBG-1	13 - 1/2"	15"	6"

DIMENSIONS

SPECIFICATIONS AND DIMENSIONAL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

